



## Impact solutions for industrial and business environments

# Compuprint

9058  
9058D

The Compuprint 9000 family is designed to meet the most demanding requirements of today's applications while offering unmatched performance in Windows and graphic printing environments. The ideal solution for mission critical requirements, with the full flexibility to support a variety of forms and documents.



### Value and Features

- Long life 24 pins print-head technology
- 480 cps at 10cpi up to 720 cps max speed
- Superior performance in volume printing
- Dual front straight paper paths
- 8 copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters

### A leading-edge series for today and tomorrow

Compuprint 9058 and 9058D integrate the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology.

It represent the preferred choice for business and industrial printing applications requiring up to 40,000 pages per month workload, providing the best investment for many years of worry free service.

### Fast, flexible, reliable

Compuprint 9058 and 9058D are built on state-of-the art technologies and innovative functionalities. With the two configurations, including the single sheet and one tractor (9058) or the dual front tractors (9058D), these models cover all the most common paper handling requirements. These models provide superior performance in traditional impact applications and high levels of flexibility and automation for the user with a unique paper path for superb reliability.

### For a broad range of connectivity and printing requirements

A large number of character sets, fonts and barcodes combined with a wide set of interfaces and protocols allow the printer to connect in most contemporary environments and to be the ideal solution for industrial requirements for printing macro characters, barcodes and pre-printed forms.



<b>Printing Technology</b>	24 pin serial dot matrix printer
<b>Printing speed</b>	Max: 720 cps · 15 cpi· 12 cpi· 10 cpi <b>Draft</b> 720 cps 576 cps 480 cps <b>LQ</b> 200 cps 160 cps 133 cps
<b>Throughput (ISO/IEC 10561)</b>	430 pph
<b>Line Length</b>	136 columns @ 10 cpi
<b>Paper handling</b>	Continuous form: front loading Front single sheet + front push tractor (9058) Dual front push tractor (9058D) Rear pull tractor (optional) (width from 76 to 432 mm - maximum thickness 0.64 mm) Automatic sheet feeder for single sheets (optional): up to three bins (120 sheets @ 80 gr/ m2 capacity each - width from 89 to 305 mm - 1+2 copies)
<b>Copies</b>	1 + 7
<b>Special functions</b>	Automatic paper path alternance Automatic Gap Adjustment (AGA) of print head based on paper thickness Zero tear-off Automatic paper parking of continuous form
<b>Graphic resolution (dpi)</b>	60, 80, 90, 120, 180, 240, 360 (horizontal) 60, 72, 180 (vertical)
<b>Vertical spacing</b>	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/ 60, n/ 72, n/ 180, n/ 216, n/ 360 per inch
<b>Horizontal spacing</b>	10, 12, 15, 17.1, 20, 24 cpi and proportional
<b>Barcodes</b>	UPC/ A, UPC/ E, EAN8, EAN13 - UPC/ EAN ADD-ON 5, UPC/ EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/ 5 Interleaved -2/ 5 Matrix - 2/ 5 Industrial - Code GP - C25-3BAR - Code BOD - 2/ 5 Bidirectional
<b>Character set</b>	<b>Standard PC IBM character sets:</b> CSI, CS2 ; 13 EPSON national variations <b>IBM and EPSON character sets:</b> CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U <b>ISO character sets:</b> 8859/ 1 (Latin1), 8859/ 2 (Latin2), 8859/ 3 (Latin3), 8859/ 4 (Latin4), 8859/ 5 (Latin/ Cyrillic), 8859/ 6 (Latin/ Arabic), 8859/ 7 (Latin/ Greek), 8859/ 8 (Latin/ Hebrew), 8859/ 9 (Latin5), 8859/ 15 (Latin9)
<b>Resident font</b>	Draft, Courier, Gothic, OCR-A, OCR-B, Script, Prestige, Presentor
<b>Resident Emulations</b>	Epson ® LQ 1050-2550 (ESC/ P), IBM ® Proprinter XL24E-L24AGM, IBM ® Personal Printer 2391+
<b>Interfaces</b>	Centronics, Parallel IEEE1284 bidirectional, Serial RS232-C, RS422-A Input buffer up to 128 Kbytes Plug&play (Windows environment)
<b>Reliability</b>	<b>MTBF:</b> 10.000 hours
<b>Print Head Life</b>	400 million characters
<b>Ribbon life</b>	Black ribbon 15 MC, Long life ribbon 20 MC (optional)
<b>Noise Level</b>	54 dBA
<b>Power Supply</b>	<b>Tension:</b> 120V - 220/ 240V <b>Frequency:</b> 60 Hz - 50 Hz
<b>Power consumption</b>	116 W Max. (printing), 22 W (standby)
<b>Physical Dimensions &amp; Weight</b>	670 (W) x 315 (H) x 320 (D) mm - 21 Kg



SFERAL WWT - Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -  
Other Countries: (+39) 011 9892 141 -  
Email: sales@sferalwwt.com -  
Website: www.sferalwwt.com -



Ordering Information

## Printers and Supplies

Compuprint 9058 (single sheet, single tractor)	PRTN958
Compuprint 9058D (dual tractor)	PRTN959
Black ribbon cartridge 15 MC	PRKN407-1
Black ribbon cartridge 20 MC	PRKN707-1
Colour ribbon cartridge 2 MC each colour	PRKN408-1

## Options

3 levels pedestal	PRFN405-0000
Floor pedestal with adjustable height setting	PRFN406-0000
Pull tractor	PRF9000
Kit for colour ribbon & long life black ribbon	KITN401-0000

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.

Copyright © 2007 Sferal wwt

ENBROOH-MAY05