



Impact solutions for industrial
and business environments

Compuprint

9060 LA
9070 LA

The Compuprint 9060LA and 9070LA are specifically designed for Compaq/Digital compatible market. Offering the choice of modern, tough, reliable and efficient printing platform where DEC ANSI compatibility is key requirement coupled to the need for a heavy duty matrix printing solution



Value and Features

- DEC ANSI PPL2, IBM Proprinter XL24E, Epson ESC / P emulations
- Long life 24 pins print-head technology
- 600/700 cps at 10cpi up to 900/1050 cps max speed
- Dual front straight paper paths
- 8 copies capability
- Simple to use, pre-set configurations
- Wide range of barcodes and macro-characters

A leading-edge series for today and tomorrow

Compuprint 9060LA and 9070LA integrate the latest technology and innovation based on more than 30 years of Compuprint leadership in the serial printer technology. These models represent the preferred choice for business and industrial printing applications requiring up to 50,000 pages per month workload, providing the best investment for many years of worry free service.

Fast, flexible, reliable

Compuprint 9060LA and 9070LA are built on state-of-the art technologies and innovative functionalities. These models provide superior performance in traditional impact applications and offer the highest levels of flexibility and automation for the user with a unique paper path for superb reliability.

Easy of use

Compuprint 9060LA and 9070LA provide the most advanced compatibility with the DEC ANSI installed base and the original DEC operability. An easy to use LCD menu gives access to all the features as paper path changes and stores macros for forms set up making the printer configuration very easy and fast.



Printing Technology	24 pin serial dot matrix printer																
Printing speed	max: 900 cps (9060LA) and 1050cps (9070LA)																
	<table border="1"> <tr> <td></td> <td>15 cpi</td> <td>12 cpi</td> <td>10 cpi</td> </tr> <tr> <td>Draft</td> <td>900/1050 cps</td> <td>720/840 cps</td> <td>600/700 cps</td> </tr> <tr> <td>NLQ</td> <td>348/390 cps</td> <td>278/315 cps</td> <td>232/260 cps</td> </tr> <tr> <td>LQ</td> <td>174/200 cps</td> <td>139/160 cps</td> <td>116/133 cps</td> </tr> </table>		15 cpi	12 cpi	10 cpi	Draft	900/1050 cps	720/840 cps	600/700 cps	NLQ	348/390 cps	278/315 cps	232/260 cps	LQ	174/200 cps	139/160 cps	116/133 cps
	15 cpi	12 cpi	10 cpi														
Draft	900/1050 cps	720/840 cps	600/700 cps														
NLQ	348/390 cps	278/315 cps	232/260 cps														
LQ	174/200 cps	139/160 cps	116/133 cps														
Throughput (ISO/IEC 10561)	500 /550pph (9060LA/9070LA)																
Line Length	136 columns @ 10 cpi																
Paper handling	Front push tractor + 2nd optional front push tractor (Width from 76 to 432 mm- maximum thickness 0,64 mm) Pull tractor (optional), 3 kind of different pedestals Automatic sheet feeder up to 3 bins (optional) (120 sheet capacity @80gr/sqm - width from 89 to 305 mm - 1+2)																
Copies	1 + 7																
Special functions	Automatic paper path alternation, Automatic Gap Adjustment of print-head (AGA), Zero tear-off (with selectable time-out), Automatic paper parking for continuous form, code update capability via parallel I/Fs, up to 4 configuration setting selectable and printable																
Graphic resolution (dpi)	60, 80, 90, 120, 180, 240, 360 (horizontal); 60, 72, 180, 360 (vertical)																
Vertical spacing	2, 3, 4, 6, 8, 12 LPI, 1, 2, 4 LPCM, n/60", n/72", n/216", n/180", n/360"																
Horizontal spacing	5, 6, 6.6, 8.25, 8.55, 9, 10, 12, 13.2, 15, 16.5, 17.1, 18, 20, 24 and Proportional																
Barcodes	UPC-A, UPC-E, EAN-8, EAN-13, Code39, Code 128, Code 93, Code 2 of 5 Interleaved, Code 2 of 5 Industrial, Code 2 of 5 Matrix, Postnet, Codabar, MSI																
Character set	IBM code Pages : CP210, CP220, USA (CP437), Greek (CP437-G), Multilingual (CP850), Eastern Europe (CP852), Turkish (CP 853), Cyrillic (CP855), Turkish (CP857), Euro PC Multilingual (CP858), Portugal (CP860), CP861, Hebrew (CP862), Canada/France (CP863), Arabic (CP864), Denmark/Norway (CP865), Russian (CP866), CP869, Abicomp, Brazilian ASCII, Mazowian, Code MJK, Bulgarian, ISO-8859-7, ISO 8859/15, ISO Latin 1T, D-Hebrew, New Hebrew - Epson National Variations: USA, France, Germany, United Kingdom, Denmark-1, Sweden, Italy, Spain-1, Japan, Norway, Denmark-2, Spain-2, Latin America, Turkey, Korea, Legal, Old Hebrew - DEC ANSI G0 char sets: US ASCII - British - DEC Finnish - French - DEC French-Canadian - German - ISO Italian - JIS Roman - DEC Norway/Denmark - ISO Spanish - DEC Swedish - Norwegian/Danish - DEC Dutch - DEC Swiss - DEC Portuguese - Legal - DEC Supplemental - DEC Spec. Graphics - DEC Technical - DEC 7Bit Hebrew - DEC Hebrew Supplemental - DEC Greek Supplemental - DEC 7Bit Turkish - DEC Turkish Supplemental - JIS Katakana DEC ANSI User Preference char sets: DEC Supplemental - DEC Spec. Graphics - DEC Technical - DEC 7Bit Hebrew - DEC Hebrew Supplemental - DEC Greek Supplemental - DEC 7Bit Turkish - DEC Turkish Supplemental - JIS Katakana - ISO Latin 1 - ISO Latin 2 - ISO Latin 5 - ISO Latin Hebrew - ISO Latin Greek - ISO Latin Cyrillic - ISO Latin 9.																
Resident font	Draft, Courier, Roman, SansSerif, Prestige, Script, Orator , OCR-A, OCR-B Download characters																
Resident Emulations	IBM XL24 E, Epson ESC/P, DEC ANSI PPL2																
Interfaces Parallel	DEC 423 Serial, Bidirectional Parallel Centronics 36 pin; serial RS232, Input buffer 32 Kbytes																
Reliability	MTBF: 10.000 hours																
Print Head Life	700 million characters																
Ribbon life	Black ribbon 15 MC, black "long life" ribbon 20 MC (optional), color ribbon (optional)																
Noise Level	<54dba																
Power Supply	from 100 to 230 V -Frequency : 60Hz / 50Hz																
Power consumption	116 W max. (printing), 22 W (standby)																
Physical Dimensions & Weight	670 (W) x 320 (H) x 450 (D) mm - 21 Kg																



SFERAL WWT - Compuprint SALES CONTACTS

Italy: (+39) 011 9892 141 -
Other Countries: (+39) 011 9892 141 -
Email: sales@sferalwwt.com -
Website: www.sferalwwt.com -



Ordering Information

Printers and Supplies

Compuprint 9060LA 1st tractor	PRT9061-LA
Compuprint 9070LA 1st tractor	PRT9071-LA
Black ribbon 15 MC	PRKN407
Color ribbon	PRKN408
Long life black ribbon 20MC	PRKN707
Color kit for color ribbon or long life ribbon	KITN401-0000

Options

Pull tractor	PRF9000
2nd tractor (4 pin)	PRFN900
base lower tractor (6 pin)	PRFN901
2nd tractor (6pin-requires PRFN901)	PRFN103
Open pedestal	PRFN405-0000
Tilt pedestal	PRFN406-0000
RapidPrint 1000 for Network connection (10Base-T)	DSTRP-FA

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.

Copyright © 2007 Sferal wwt

ENBROCH-MAY05