


## Compuprint 4247-X03 Multiform Printer



Compuprint 4247-X03



# Industrial

### Reliable high-speed printing for demanding business environments

#### High reliability—Low cost of ownership

Designed for high output performance in demanding print environments “from the office to the warehouse” the Compuprint 4247 industrial strength printer provides professional reliability at a cost of ownership that is surprisingly attractive. With an impressive functional lifetime, low per-page costs, and worry free operation, impact printers from Compuprint continue to deliver business value that laser printers simply cannot match. For mission-critical applications where reliability is paramount, or when the cost of printing is a concern, the Compuprint 4247-X03 is ready to support core business needs and protect the bottom line.

#### Fast speed, broad functionality

With print speeds up to 800 cps<sup>1</sup>, and up to two straight continuous form paper paths for outstanding paper-feeding reliability, the Compuprint 4247-X03 is built to deliver dynamic performance in the most demanding and rigorous environments. Optional dual front paper paths and heavy-duty 6-pin tractors provide easy forms loading and support for printing on a wide range of media types.

### HIGHLIGHTS

- Fast, quiet, reliable printing at up to 800 characters per second<sup>1</sup> on up to 8 part forms
- Rugged design for superior durability in rigorous environments
- Pedestal or desktop configuration
- Optional integrated Ethernet with support for IPDS™
- Automatic forms loading and thickness adjustment



# Industrial

## Boost efficiency with powerful remote printer management

The Remote Printer Management Utility, included with the optional Ethernet controller, gives users visibility to real-time printer status for every printer on the network, remote configuration of multiple printers simultaneously, and remote full function access to a virtual operator panel.

## Adaptable to your business needs

The combination of paper parking, switching and linking can help you maximize your printing options and increase productivity. The all-points-addressable graphics capability enables quality printing of bar codes, logos, overlays and more. To enable the migration from legacy attachments, the integrated Ethernet card supports IPDS and SNMP. For optimal placement flexibility, pedestal or desk-top configurations are available.

## Easy to use and efficient

Automatic forms loading and thickness adjustment, along with customizable intelligent forms handling enable highly efficient forms loading and retrieval. Additionally, the new user-friendly operator panel features an intuitive design for efficient navigation and a multilingual 2x24 LCD display for easy to read menus and messages.

## Rely on Compuprint, supplies and experience

In addition to the standard warranty, Compuprint offers comprehensive service and support that extends your coverage. For more information contact local distributor or visit the web at:

[www.compuprint.com](http://www.compuprint.com)

## Compuprint 4247-X03 Multi-Form Printers at a glance

<b>Max. Print Speed<sup>1</sup> (at 10dpi)</b>	Data processing mode 800 cps DP text mode 400 cps NLQ mode 200 cps
<b>Print options</b>	13.6"/345.44 mm maximum print line Vertical spacing: 6 or 8 lpi selectable from operator panel for text 3, 4, 6, 8 or 9 lpi selectable under program control for text 1/144" increments under program control available for graphics Horizontal spacing: 10, 12, 15, 16.7, 17.1 and 20 cpi Proportional spacing is available in DP text and NLQ mode
<b>Bar Codes</b>	UPC-A, UPC-E, UPC-2, UPC-5, EAN-8, EAN-13, Code 3 of 9, Code 128, Interleaved 2 of 5, Industrial 2 of 5, Codabar, MSI and Matrix 2 of 5
<b>Paper handling</b>	Support for two continuous forms paths Dual front tractors Paper parking, switching and linking Automatic forms loading and thickness adjustment
<b>Paper Sizes</b>	Continuous forms: 3" to 17" (76 mm to 432 mm) width, 3" to 24" (76 mm to 610 mm) length
<b>Emulations</b>	Standard: Epson FX, IBM Proprinter 4202 III XL and IBM 2381 Personal Printer and native 4247 mode Optional Ethernet IPDS: IBM 4224, IBM 4230 and native 4247 mode
<b>Interfaces</b>	Centronics Parallel, Serial (RS-232C), USB 2.0, Ethernet 10/100 BaseT
<b>Input Buffer</b>	up to 128Kb
<b>Drivers</b>	Windows ® 2000, XP, VISTA, Win7 (32 and 64 bit)
<b>Physical characteristics</b>	WxDxH: 26.4" x 17.7" x 12.6" (670 mm x 450 mm x 320 mm) 46.3 lb./21 kg (weight)
<b>Environmental conditions</b>	Relative Humidity: 40% to 60% (non condensing), RH Temperature: 50° to 104°F (10° to 40°C) Operating Relative Humidity: 5% to 95% (non condensing), RH Temperature: -31°F to 149°F (-35° to 65°C) Storage Acoustics Printing (in DP text mode): 4247-X03: 55.7 dBA
<b>Power Voltage</b>	90 to 244 Vac
<b>Power Frequency</b>	50/60 Hz
<b>Power Consumption</b>	Maximum, 220 Watts, Typical 155 Watts, Power Saver Mode 20 Watts
<b>Heat Output</b>	147 W typical (500 BTU/hr), 23 W Idle (75 BTU/hr)
<b>Workload<sup>2</sup></b>	57.000 pages per month
<b>Throughput</b>	660 pages per hour (ECMA 132)
<b>Rated Printhead Life</b>	800 million draft characters
<b>Consumables<sup>3</sup></b>	25 million characters black ink ribbon
<b>Reliability MTBF</b>	20.000 hours at 25% D.C.

---

## ENDNOTES

- <sup>1</sup> Exact speed varies depending on document complexity, system configuration, software application, driver and printer state.
- <sup>2</sup> The maximum workload is calculated at rated duty cycle (4 hours a day for 22 days month)
- <sup>3</sup> Ribbon life depends on many factors, including printer condition, machine settings, paper quality and bar code. For optimum printer performance use only genuine consumables Compuprint
- 

## Ordering Information

### Printer

4247-X03 Multiform Printer 44D8400-C

### Controller Interface (initial)

4247-X03 SBCS Controller with Parallel/Serial/USB 44D8403-C

4247-X03 SBCS Controller with Parallel/Ethernet 10/100 44D8406-C

4247-X03 SBCS Controller with Parallel/Ethernet 10/100 IPDS 44D8409-C

### Options Finishing

4247-X03 Front second tractor - 6 pin 44D8978-C

4247-X03 Printer Stand 44D8973-C

### Supplies

4247-X03 Black ribbon (25MC) 57P1743-C

---

© Copyright Compuprint srl Printed  
In Italy 2011

All rights reserved. All other  
company and product names are  
Trademarks or registered  
trademarks of their respective  
owners.

Subject to change without notice.

Version: 1.1 - 16.02.2012

**MAN-10312.00.00**



### Compuprint Commercial Contacts

Italy: Tel: +39 0119892 133

Fax :+39 011 9974432

Email: sales@compuprint.com

Internet: www.compuprint.com

